Hammer Drill 16 mm (5/8")
HP1640 / HP1640F / HP1641 / HP1641F

BIG PERFORMANCE AND CONVENIENCE

Photo : HP1641F

High Maneuverability and Long Life

Change lever to select the working mode

Rotation only



Rotation with hammering



HP1641/F: Keyless Chuck
HP1640/F: Keyed Chuck

Neck diameter: 43mm
This tool can be attached to Type 43 Drill Stand.

Added rubberized portion for sure inline grip to obtain maximum power thrust

F/R Change system by brush holder unit system provides the following features.

- Extended service life of carbon brush
- Same power even in the reversed rotation

Variable speed control switch with big trigger

Lock-on button
for continuous operation

Ergonomically designed soft grip
provides more control and comfort while minimizing hand fatigue and pain.

Photo: HP1641F

LED job light

Accessories

Type 43 Drill Stand
Part No. A-36712

Hammer Drill

- Double Insulation
- Variable Speed
- Reversing
- Keyless Chuck (HP1641, HP1641F)
- Built-in Job Light (HP1640F, HP1641F)

HP1640F

HP1641F

HP1640/F HP1641/F 16mm (5/8")

Continuous rating Input	*680W*
Capacity	***Concrete :*** *16mm (5/8")*
	Steel : *13mm (1/2")*
	Wood : *30mm (1-3/16")*
Impacts per minute (ipm)	*0-44,800*
No load speed (rpm)	*0-2,800*
Dimensions	*303 x 72 x 222mm*
(L x W x H)	*(11-7/8" x 2-13/16" x 8-3/4")*
Net weight	*1.8kg (4.0lbs)*
Power supply cord	*2.0m (6.6ft)*

Standard Equipment
Side Grip, Depth Gauge, Chuck Key (HP1640/F)

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z23417-2 AI-BA